



EFFICIENT AND COST-EFFECTIVE LED BOLLARDS FOR THE ILLUMINATION OF GROUND SURFACES. IT IS CHARACTERISED BY HIGH LUMINOUS EFFICIENCY AND GREAT UNIFORMITY OF ILLUMINANCE. ITS STURDY CONSTRUCTION MAKES IT ESPECIALLY

SUITABLE FOR AREAS IN WHICH CONSIDERABLE ROBUSTNESS IS REQUIRED. WASH LIGHTING WITH A WIDE BEAM, ASYMMETRICAL AND ROTATIONALLY SYMMETRICAL LIGHT DISTRIBUTION FOR THE ILLUMINATION OF PATHWAYS, ENTRANCE AREAS AND DRIVEWAYS IN PRIVATE AND PUBLIC AREAS

H 60,4 CM



Ø 16 CM

#### BALDUR

DIE CASTING ALUMINIUM LED BOLLARD  
DIFFUSER IN CLEAR POLYCARBONATE  
20W LED  
AC 220-240V INPUT  
H 60,4 X BASE Ø 16 CM  
LUMEN 2100  
IP65 - BEAM ANGLE 360°  
NOT DIMMABLE  
KELVIN 2700

BLACK NO. 845-001



#### BALDUR SHIELD

BLACK NO. 845-002