

# Dot 800

design Foster + Partners, 2015

release 2019, December



Suspended lamp for indirect lighting with integrated LED source and diffused light optic system.


Aluminium structure with steel matt-painted reflector.


1-10V dimming or DALI dimming available.

The decentralizing kit is always included.

## Finishing

### Standard

 Anodised black  
cod. 131D01XO00

 Anodised brass  
cod. 131D50XO00

All RAL coating and galvanic finishes available upon request

## Light emission

- Light emission: diffuse
- Light direction: indirect downlight
- Light source: led board
- Source flux: 3250 lm
- Emitted flux: 1780 lm
- Efficacy: 43 lm/W
- CCT: 3000K
- CRI index: 83
- Lifetime: >50000h L70 @ 25°C

## Electrical Facts

- Source power: 39 W
- Power absorption: 41 W
- Stand-by absorption: < 2 W
- Grid voltage: 100-240V AC/50-60 Hz
- Power supply: internal AC-DC converter provided
- Dimmability: 1-10V, DALI dimmable
- Energy class: A++

## Technical data

- Environment: indoor
- Placement: pendant
- Net weight: 7,7 Kg
- Certifications: CE
- Suggested ambient T: 25°C
- Maximum ambient T: 40°C
- Insulation class: I
- Protection class: IP20

Packaging  
cardboard box  
90 x 90 x 28 (cm)  
0,30 m<sup>3</sup>

Gross weight  
18 Kg

