

Wall back plate fixing

Additional comments

Technical Data Sheet

| sear crimerre | | rechnical Data Sheet | | | | |
|-----------------------------|--|--|--------------|---------------------------------------|---|--|
| Product number | | 10425-5GO | | Professional image / Primary image | Technical 2D/3D Line Drawing with Measurements | |
| Date: | | 17/11/2025 | | • | 150 | |
| Product range | | Heritage | | | cul | |
| Product name | | Heritage 5Lt Pendant, Gold Metal and Clear Glass Drops | | | 1500 | |
| Application | | Ceiling | | | 400 | |
| Barcode | | 5053423273464 | | | ### ################################## | |
| Product Details | | | Base Details | | | |
| Primary material Mild Steel | | Base dimensions (mm) | | | | |
| Secondary material | | Links describe | | | | |

| Dai oodo | | 10000 12027 0 10 1 | | | _ 0500 _ | |
|------------------------------------|---------------|--------------------------------|---|------------------|------------------|--|
| Product Details | | • | Base Details | | | |
| Primary material | Mild Steel | | Base dimensions (mm) | | | |
| Secondary material | Glass | | Light details | | | |
| Colour | Gold | | Primary lamp holder | | G9 | |
| Finish | Painted | | Primary lamp holder number of lamps | | 5 | |
| Total height (mm) | 1000 | | Primary lamp type | | G9 Halogen | |
| Height (mm) | 450 | | Primary lamp included | | No | |
| Width (mm) | 500 | | Secondary lamp holder | | - | |
| Length (mm) | 500 | | Secondary lamp holder number of lamps | | | |
| Projection (mm) | NA | | Secondary lamp type | | - | |
| Shade/glass/diffuser colour | Clear | | Primary lamp lumens | | | |
| Shade/glass/diffuser finish | - | | Secondary lamp lumens | | | |
| Shade/glass/diffuser material | Glass | | Class | | 1 (Earthed) | |
| Shade/glass/diffuser style | - | | Colour temperature (K) | | NA | |
| Cut out (mm) | | | CRI | | | |
| Recess depth (mm) | | | Beam angle (degrees) | | | |
| Fire rated | - | | Electrical details | | • | |
| IP rating | IP20 | | Primary lamp wattage | | 33W | |
| Bathroom zones | - | | Secondary lamp wattage | | | |
| Tilt angle (degrees) | - | | Operating voltage | | 220-240V~50/60Hz | |
| Height adjustable | Yes | | Transformer/driver details | | | |
| Adjustable details | Height adjust | able by 3 support wires ,cable | Dimmable | | - | |
| Max drop for ceiling fittings (mm) | 1000 | | Dimming method | | NA | |
| Minimum drop for ceiling fittings | 450 | | Switched | | - | |
| (mm) | | | Switch location | | - | |
| Energy class | N/A | nd LED Broducto 1 Voor | Switch type | | - | |
| Warranty details | Warranty | ed LED Products - 1 Year | Plug details | | NA | |
| Efficacy (Im/w) | | | Supply cable total length (mn | n) | | |
| Ceiling cup / Back plate details | | | Supply cable colour | | Clear | |
| Ceiling cup dimensions (mm) | D:120x H:25 | | Chain length from ceiling cup to lampholder (mm) | | | |
| Ceiling cup details | | | Supply cable length from base/lampholder to switch (mm) | | | |
| Ceiling cup shape | Round | | Supply cable length from swi | tch to plug (mm) | | |
| Ceiling cup colour | Gold | | Packaging details | | | |
| Ceiling cup finish | Painted | | | | 0.43 | |
| Ceiling cup material | Metal | | Unit box length (metres) | | 0.59 | |
| Ceiling cup fixing | 2 Fixed Screv | ws | Unit box width (metres) | | 0.31 | |
| Wall back plate dimensions (mm) | | | Unit box net weight (kg) | | 4.49 | |
| Wall back plate shape | - | | Unit box gross weight (kg) | | 6.14 | |
| Wall back plate colour | - | | | | | |
| Wall back plate finish | - | | | | | |
| Wall back plate material | <u> </u> | | | | | |
| | | | 7 | | | |

(Default)