



## TECHNICAL DATA

|                                       |                   |
|---------------------------------------|-------------------|
| Item no.                              | 1007145           |
| Number of different light outlets     | 2                 |
| IP Code                               | IP 65             |
| Impact resistance class               | IK 08             |
| Impact resistance                     | 5 Joule           |
| Assembly                              | Surface           |
| Assembly details                      | Wall              |
| Number of through-wires               | 71                |
| Primary nominal voltage               | 220-240V ~50/60Hz |
| Secondary power / voltage             | 275 mA            |
| Safety class                          | I                 |
| Wattage                               | 9.3 W             |
| Minimum ambient temperature           | -20 °C            |
| Maximum ambient temperature           | 45 °C             |
| Operating efficiency (LOR)            | 0,72              |
| Number of luminaires at LS B16A       | 71                |
| Number of luminaires at LS C16A       | 118               |
| Temperature at glass (light emission) | 45 °C             |
| Stroboscopic effect (SVM)             | 0                 |
| Lumen                                 | 860 lm            |
| Colour temperature                    | 2700/3000 Kelvin  |
| Color                                 | white             |

## Light Source



|              |          |
|--------------|----------|
| CRI          | 80       |
| LXXBXX data  | L70B50   |
| Risk Group   | 1        |
| Width        | 17.5 cm  |
| Height       | 9 cm     |
| Depth        | 3.1 cm   |
| Net weight   | 0.6 kg   |
| Gross weight | 0.642 kg |