FLOS

BON JOUR UNPLUGGED COP

Designed byPhilippe Starck, 2015



Main Information

| Ean | 8059607071007 |
|--------------------------|---|
| Custom product | No |
| Mounting | Table |
| Number of lamps | 1 |
| Light source type | LED |
| Light source replaceable | Replaceable (LED only) light source by a professional |
| LED type | LED Module |
| Source flux (Im) | 150 |
| System flux (Im) | 150 |

Downloads

| Mounting instructions | PDF ± |
|-----------------------|-------|
| Spare Parts SVG | svg ± |

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class G



Replaceable (LED only) light source by a professional

©2025 Flos - P.IVA 00290820174 - 6/4/2024 - In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warrantly in any way.

Optical

| Number of lamps | 1 |
|-----------------------|----------------|
| Lighting type | Direct |
| Optical type | Diffused light |
| Lighting distribution | Roto symmetric |

Electrical

| Power supply | Remote excluded |
|---------------------------|---|
| Insulation Class | III |
| Main voltage (Vac) | 5 |
| Dimming | Yes |
| Power (W) | 3 |
| Charging min time | 3 |
| Batteries inside | Yes |
| Battery type | LI-IO |
| Charging socket/connector | USB-C |
| Induction recharge QI | Yes |
| Charging cycle guaranteed | 500 |
| Dimming interface | Dimmer Integrated |
| Light source replaceable | Replaceable (LED only) light source by a professional |
| Light source type | LED |
| LED type | LED Module |
| CCT (K) | 2200-2700-3000 |
| Source flux (Im) | 150 |
| System flux (Im) | 150 |
| LOR (%) | 100 |
| LED Life / Failure Ratio | 30000.000 |
| CRI | 90 |

Physical

| Height (mm) | 270 |
|-------------|-------|
| Height (in) | 10.63 |

Logistic

| Net weight (kg) | 0.55 |
|----------------------------|-------|
| Net weight (lb) | 1.21 |
| Gross weight (kg) | 0.85 |
| Gross weight (lb) | 1.87 |
| Shipping packages quantity | 1 |
| Package height (mm) | 170 |
| Package height (in) | 6.69 |
| Package width (mm) | 230 |
| Package width (in) | 9.06 |
| Package length (mm) | 375 |
| Package length (in) | 14.76 |

Marking

| IP Category | 20 |
|--------------|----|
| Energy Label | G |

©2025 Fios - P IVA 00290820174 - 6/4/2024 - In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warry way.