



WEVER & DUCRÉ
LIGHTING

CORK 1.0

210163B2

Project

Type

Notes

Quantity

Date

GENERAL

Ceiling

Suspended

Jet Black

IP20

Interior

180 lm

9005^a

LED

2700 K

3-step binning

OPTICAL

opal

PHYSICAL

Diameter 28 mm

Height 55 mm

0.24 kg

incl. 2.5 m suspension

ELECTRICAL

incl. power supply


120 - 240 V

Total connected power 3 W

PC1

Safety distance 0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.





WEVER & DUCRÉ
LIGHTING

CORK 1.0

210163B2

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	1.0	0.95	0.91	0.87	0.83
LSF	1	1	1	1	1

MF LMF × RSMF × LLMF × LSF RSMF^a Room Surface Maintenance Factor
 MF Maintenance Factor LLMF Lamp Lumens Maintenance Factor
 LMF^a Luminaire Maintenance Factor LSF Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

OPTICAL

Bottle 1

TYPE	Ø · H (MM)	ORDERCODE
CORK	ø75-174	9 0 0 1 9 0 1 3

Bottle 2

TYPE	Ø · H (MM)	ORDERCODE
CORK	ø87-323	9 0 0 1 9 0 1 4