



## SLC LED STRIP TW CV 168 10M 12MM 12,5W 1300LM 827/65 IP

14/01/2022

### S14052

## Product description

Tunable White technology is a good solution, whenever standard white colour temperatures are not enough. This LED-strip combines 2 types of diodes: 2400K and 6500K, which gives a Tunable white light. 10 meters on one single connection.

Tunable White technology is a good solution, whenever standard white colour temperatures are not enough. This LED-strip combines 2 types of diodes: 2400K and 6500K, which gives a tunable white light spectre. Changing light temperature from ultra warm 2400K to day-like 6500K will modify rooms ambient. Adjust light colour temperature as you desire with our user friendly stand-alone controls, which fit any installation. Suitable in any solution, as direct, decorative and background light. 168 LED diodes per meter give smooth and uniform linear light. Shall be installed in aluminum profiles, to ensure sufficient cooling and long product lifetime. 10 meter on a single connection.

## Technical data

<b>Model</b>	Strip	<b>Mounting method</b>	Surface mounting/recessed mounting
<b>Lamp type</b>	LED not exchangeable	<b>Number of nodes per meter</b>	168
<b>Lamp power per meter</b>	12,5 W	<b>Luminous flux per meter</b>	1300 lm
<b>Voltage type</b>	DC	<b>Lamp voltage</b>	24 - 24 V
<b>Beam angle</b>	120 °	<b>Type of control gear</b>	LED operating device voltage-controlled
<b>Rated life time L80/B10 at 25 °C</b>	60000 h	<b>Protection class</b>	II
<b>Max. system power</b>	125 W	<b>Colour of light</b>	White
<b>Colour temperature</b>	2700 - 6500 K	<b>Colour rendering index CRI</b>	80-89
<b>Power factor</b>	0,95	<b>Width</b>	14 mm
<b>Height/depth</b>	1,6 mm	<b>Length</b>	10000 mm
<b>Length of particular segments</b>	71,4 mm	<b>With connection set</b>	Yes
<b>Type of wiring</b>	Ending	<b>Number of poles</b>	3
<b>Conductor cross section</b>	0,35 mm <sup>2</sup>		





<b>Max length per connection:</b>	10 meter
<b>3M adhesive tape</b>	Yes
<b>Dimmable</b>	Yes

<b>LED-Strip length (m)</b>	10
<b>Operating temperature</b>	-20°C ~ +45°C
<b>Dimming method</b>	Pulse Width Modulation (PWM)
<b>Dimming range</b>	1-100%