



SLC SmartOne Power Supply CV 24V 75W RGB/RGBW Zigbee

14/01/2022

S32056



Product description

RGB / RGBW 24V, 75W PSU with built-in PWM dimmer
 Based on the latest Zigbee 3.0 protocol
 Works stand-alone when connecting a push switch or wirelessly via TouchLink to a remote control/switch
 Supports TouchLink communication with Zigbee remotes and switches
 Compatible with most smart home systems

Technical data

Model	Static
Housing	Plastic housing
Output voltage	24 - 24 V
Output power	75 - 75 W
Protection class	II
Width	64 mm
Output type	Constant voltage (CV)
Output power per channel (W)	-
Tunable White	Yes
RGBW	Yes
Frequency range (Hz)	50 - 60
Inrush Current (A)	2
Exterior color	White
Expected lifetime (Hours) (Ta 45°C)	50000

Dimming Zigbee	Yes
Suitable for constant voltage	Yes
Output current	- 2 mA
Degree of protection (IP)	IP20
Length	244 mm
Height	32 mm
Number of LED Output Channels	4
Mono	Yes
RGB	Yes
Input voltage (V)	100 - 277
Power factor	0,95
Strain relief	Yes
Operating temperature	-20°C ~ +45°C
Tc (°C)	85





Dimming method	Pulse Width Modulation (PWM)
Dimming curve (LED)	Logarithmic
Brand	SLC
HS Code	85041080

Dimming interface	Zigbee
Dimming range	0-100%
Produced by	The Light Group