

Luminaire

 Code TRU LWW 25
 Name Tru Floor 36W

Measurerm.

 Code TRUF032019
 Name Tru Floor 36W

Luminaire Flux	3545.07 lm	Luminaire Power	36.00 W	Efficacy	98.47 lm/W	Efficiency	100.00%
Lamps Flux	3545.00 lm	Maximum value	313.45 cd/klm	Position	C=90.00 G=142.00	CG	Asymmetrical
Rectangular Luminaire		Length	100 mm	Width	100 mm	Height	2000 mm
Rectangular Luminous Area		Length	100 mm	Width	100 mm	Height	0 mm
Horizontal Luminous Area		0.010000 m2		Emitting area on Plane 180°		0.000000 m2	
Emitting area on Plane 0°		0.000000 m2		Emitting area on Plane 270°		0.000000 m2	
Emitting area on Plane 90°		0.000000 m2		Glare area at 76°		0.002419 m2	
Coordinate system		CG		Symmetry Type		Asymmetrical	
Date		27-01-2000		Maximum Gamma Angle		180	
Measurement Distance		0.00		Measurement Flux		3545.00 lm	
Operator				Source Voltage [V]		230.00 V	
Temperature		25.00 °C		Source current [A]			
Humidity		60.00 %		Photocell			
Notes							

Line	Code Led	Luminaire Lamps		Flux [lm]	Pow. [W]	Q.ty
		Name Led	Flux [lm]			
C.I.E.	9 33 66 33 100		D DIN 5040	3545.00	36.00	1
F UTE	--		B NBN	D12 BZ 10		

