FLOS

LUCE SFERICA S3 EU/CCC

Designed byRonan Bouroullec, 2025



Main Information

| Ean | 8059607075722 |
|--------------------------|---|
| Custom product | No |
| Location | Indoor |
| Environment | Indoor dry location |
| Mounting | Suspension |
| Light source type | LED |
| Light source replaceable | Replaceable (LED only) light source by a professional |
| LED type | LED Module |
| System flux (Im) | 8,018 |

Downloads

Mounting instructions

PDF ±

Ecodesign and Energy Labelling

This product contains a light source of energy efficiency class F



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

©2025 Flos - P.IVA 00290820174 - 6/4/2024 - In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product our receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warrantly in any way.

Optical

| Lighting type | Indirect, Direct |
|-----------------------|------------------|
| Optical type | Diffused light |
| Lighting distribution | Symmetric |

Electrical

| Frequency (Hz) | 50/60 |
|--------------------------|---|
| Power supply | Integrated |
| Power supply type | Dimmer on board |
| Power supply replaceable | Replaceable control gear by a professional |
| Insulation Class | <u> </u> |
| Main voltage (Vac) | 100-240 |
| Dimming | Yes |
| Power (W) | 165 |
| LED current (mA) | 700 |
| Power factor (W) | 0.96 |
| Dimming interface | Dimmer Integrated |
| Light source replaceable | Replaceable (LED only) light source by a professional |
| Light source type | LED |
| LED type | LED Module |
| CCT (K) | 2700 |
| System flux (Im) | 8,018 |
| LOR (%) | 100 |
| CRI | 95 |

Physical

| Suspension type | Suspension steel cable |
|---|------------------------|
| Cord length (mm) | 2700 |
| Cord length (in) | 106.299 |
| Canopy length/diameter (mm) | 1316 |
| Canopy length/diameter (in) | 51.811 |
| template.product.physical.canopy. widtd class="table-lable" | 78 |
| template.product.physical.canopy. widtd class="table-lable".us | 3.071 |

Logistic

| Net weight (kg) | 41 |
|----------------------------|--------|
| Net weight (lb) | 90.39 |
| Gross weight (kg) | 51.6 |
| Gross weight (lb) | 113.76 |
| Shipping packages quantity | 3 |

Marking

| IP Category | 20 |
|--------------|----|
| Energy Label | F |
| Casambi | No |

©2025 Flos - P IVA 00290820174 - 6/4/2024 - In our constantly evolving world and business, technical upgrades happen every day. This means all product specifications and data are subject to change without warning in order t improve reliability, function, performance or otherwise. We make every effort to ensure the accuracy of our product images, however due to different lighting and screens used for viewing, the colours may vary. Images are indicative of the quality and style of the product but may not represent the precise details of the product you receive. This is because we are constantly working to make improvements. For aesthetic reasons, cables and/or electrical elements are often not shown. Refer to technical data sheets for all technical data. Images and colours are not part of any contract or warrantly in any way.