



WEVER & DUCRÉ
LIGHTING

RAY mini 2.0

301220B0

Project
Type
Notes
Quantity
Date

GENERAL

Wall
 Surface
 Jet Black
 IP20
 Interior
 Indirect 405^a, 440^b, 445^c lm
 Direct 405^a, 440^b, 445^c lm
 Total 810^a, 880^b, 890^c lm
 9005^d

LED

Lamp 2 x PARI6
 PARI6
 Socket GU10
 max. 12 W
 L70 / 50000 h

OPTICAL

Wide Flood



PHYSICAL

Diameter 67 mm
 Height 200 mm
 0.36 kg


ELECTRICAL

100 - 240 V
 Total connected power 15^c, 16^b, 18^a W
 PC1
 Safety distance 0.3 m

- ^a LED 1800-2850K CRI 90 silver
- ^b LED 3000K CRI 80 white
- ^c LED 2700K CRI 80 white
- ^d RAL Palette colors may deviate slightly due to production conditions.



LIGHT DISTRIBUTION



[301220B0] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.
 © Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



WEVER & DUCRÉ
LIGHTING

RAY mini 2.0

301220B0

LED LAMPS

PAR16 LED Lamp

TYPE	COLOUR	Ø·H (MM)	ORDERCODE
2700K >90 CRI GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 3
3000K >90 CRI GU10	Jet Black	ø50-58	9 0 1 2 2 8 B 5
2700K >80 CRI GU10	Signal White	ø50-58	9 0 1 2 2 8 W 2
2700K >90 CRI GU10	Signal White	ø50-58	9 0 1 2 2 8 W 3
3000K >80 CRI GU10	Signal White	ø50-58	9 0 1 2 2 8 W 4
2700K >80 CRI GU10	Silver/Grey	ø51-55	9 0 5 2 2 7 S 2
3000K >80 CRI GU10	Silver/Grey	ø51-55	9 0 5 2 2 7 S 4

PAR16 LED Lamp | Ambient

TYPE	Ø·H (MM)	ORDERCODE
1800-2850K >90 CRI GU10	ø50-58	9 0 1 2 2 9 S 9