

designTommaso Cimini, 1984

release 2019, December













Floor lamp for direct and indirect lighting with single pivotable arm. The head can rotate 180° and is provided with a screen grid for glare control. Equipped with a foot on-off and dimmer switch.

Finishing


Standard

Black soft touch cod. 61L01ST00

Special

Metallic bronze cod. 61L29MT00

Matt white cod. 61L02OP00



All RAL coating and galvanic finishes available upon request

Light emission

- · Light emission: diffuse
- Light direction: downlight, uplight UGR: < 19
- Light source: 2 led boards
- Source flux: 3980 lm
- Emitted flux: 2346 lm
- Efficacy: 49 lm/W
- CCT: 3000K
- CRI index: >97
- Lifetime: >55000h L80 @ 25°C

Electrical Facts

- Source power: 45 W
- Power absorbtion: 48 W
- Stand-by absorbtion: < 1 W
- Grid voltage: 100-240V AC/50-60 Hz (EU/UK plug equipped)
- Power supply: internal AC-DC converter provided
- Dimmability: on-wire foot dimmer switch
- Energy class: A++

Technical data

- Environment: indoor
- · Placement: floor
- · Net weight: 6,8 Kg
- · Certifications: CE
- Suggested ambient T: 25°C
- Maximum ambient T: 40°C
- Insulation class: II
- Protection class: IP20

Packaging cardboard box 211 x 33 x 13 (cm) 0,127 m³

Gross weight 9,3 Kg



