


Pendant Luminaires | 220-240 V
topLED 35 W DC 700 mA | CRI 90
8680



Technical data	
Construction year	2019
Type	Pendant Luminaires
Installation position	Ceiling
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	35 W
Source lumens	3523 lm
Frequency	50 - 60 Hz
CCT / Tone	2700 K
Colour rendering index	90 Ra
C.C. / C.V.	AC
Safety class	1
IP	IP20
Glow wire test	850°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	Phase cut
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	2500 m
Resin potting	No
Type of light emission	Double emission
Electrostatic discharge protection	No
Surge protection	No

Finishing diffuser	
Material	PC
Colour	white

Finishing mounting frame	
Material	Die-cast Aluminium
Colour	embossed white RAL 9003

Cables Pendant Luminaires	
Max cable length	2500 mm



Pendant Luminaires | 220-240 V | topLED 35 W DC 700 mA | CRI 90
8680

Double emission pendant luminaires for indoor application. The warm white LED light source with a general lighting light distribution is composed of 180 topped LEDs with CCT of 2700 K and a CRI 90; the source luminous flux is 3523 lm, with a 100.7 lm/W nominal luminous efficacy.


The diffuser is made of PC; the mounting frame is made of die-cast aluminium, with a embossed white ral 9003 finish. The ingress protection degree is IP20;

The total absorbed power is 35 W. The power supply cable is included and features a 2500 m lenght.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Source lumens	3523 lm
Colour temperature	2700 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	90 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25
LED Life / Failure Ratio	
L70 B20 C0 72.5h (at Tj 115 Ta 25)	



Dimmer
220-240V

Code
KIT0026



Dimmer
Radio-frequenza, 85-240V

Code
KIT0080