




Ray Floor 1

by Rodolfo Dordoni , 2006



Floor lamp providing diffused lighting. Steel tube (10 mm diam.) structure, welded, brushed and chrome-plated. Diffuser support disk in die-cast, polished and chrome-plated Zamak alloy. Injection-molded PA6 (nylon) lamp-cover. Color: white. Injection-molded PC (polycarbonate) inner diffuser. Color: 3% opal. Injection-molded elastic PVC (polyvinylchloride) feet. Lathe-shaped aluminum diffusers, painted white on the inside, and shiny white or black on the outside or gray-colored, blown and overlaid glass with glossy external finish. On the cable there is the electronic dimmer which allows the regulation of light brightness.



Mounting	Floor
Environment	Indoor
Weight	5.0 (met) - 8.0 (glass) Kg
Light sources available	1 x LED 8W E27 740lm 2700K [e] cod. RF25323 Dimmable 1 x LED 8W E27 740lm 3000K [e] cod. RF25317 Dimmable
Emergency	Without
Switching	On the cable there is the electronic dimmer which allows the regulation of light brightness with a dial.
Dimmer	Included
Voltage	220-240V
Power	MAX 150W
Battery	No
Supply included	Yes
Cord Length	2300 mm
Materials	Aluminum, Glass, Steel
Colors	● F5916030 - Black ● F5916009 - White ● F5915020 - Glass
Certificate	