



WEVER & DUCRÉ  
LIGHTING

# LEENS 2.0

311274B5

Project
Type
Notes
Quantity
Date

## GENERAL

Wall
Surface
Jet Black
IP20
Interior
Indirect 275 lm
Direct 275 lm
Total 550 lm
9005 <sup>a</sup>

## LED

3000 K
CRI 90
L95 / 50000 h
3-step binning

## OPTICAL

Wide Flood
------------



## PHYSICAL

Length 130 mm
Width 130 mm
Height 30 mm
0.9 kg


## ELECTRICAL

incl. PS   phase-cut dim
220 - 240 V
Total connected power 7.5 W
PC1
Safety distance 0.3 m

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.



## LIGHT DISTRIBUTION



[311274B5] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for December 15, 2020 the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply.  
© Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com



**WEVER & DUCRÉ**  
LIGHTING

# LEENS 2.0

311274B5

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.