

PRODUCT NO. 1946-0FW100

DOTLUX LED-Deckeneinbaustrahler FLEXA COLORselect, POWERselect 28W/38W 60° schwenkbar



to the product page

- Ausgestattet mit innovativen SAMSUNG® LEDs
- Wärmeentkoppelter Treiber in einem separatem Gehäuse
- Hocheffizienter, passiver Alu-Druckguss Kühlkörper
- Gleichmäßige Lichtverteilung durch die spezielle Streuscheibe
- Leichter Austausch durch Standardgröße

WEIGHT IN KG	1.3
POWER CONSUMPTION IN WATTS	38
CONSUMPTION (KWH/1000H)	38
NET LUMINOUS FLUX IN LUMENS	max. 4180
LUMEN PER WATT	110

Dimensions

length: 240mm
width: 145mm
height: 103mm

BEAM ANGLE	100°
DIMMABLE	not dimmable
TURN- /SWINGABLE	60° / -
ENABLED LICENSED PRODUCT	Yes
INSTALLATION OPENING WIDTH IN MM	130
INSTALLATION OPENING LENGHT IN MM	227
COLOR-RENDERING-INDEX	CRI > 92
FREQUENCY RANGE IN HZ	50/60
WARRANTY	5 years
L/B VALUE	L80/B10
LIFETIME	approx. 50.000 h at 25°C
LIGHT COLOR	warm white/neutral white/daylight white
POWER FACTOR	0,9
SWITCH CYCLES	> 100.000
IP-PROTECION	IP20
PROTECTION CLASS	II
ASSORTMENT	Proline
TEMPERATURE RANGE	-20°C to +40°C