



CONCRETO L

WL recessed wall light grey, 12W, 570lm, 3000K

A high-quality feature made from fashionable concrete: the rectangular CONCRETO L wall-mounted light adds a fresh touch to outdoor areas. With a colour temperature of 3000 Kelvin, the integrated LED bulb emits an inviting, warm white light with a particularly sustainable lifespan of 50,000 hours. The grey concrete lamp has an IP65 protection class rating that offers protection in any weather.

TECHNICAL DATA

| | |
|---------------------------------------|-------------------|
| Item no. | 1006405 |
| IP Code | IP 65 |
| Impact resistance class | IK 03 |
| Impact resistance | 0.35 Joule |
| Assembly | Surface |
| Assembly details | Wall |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 700 mA |
| Safety class | II |
| Wattage | 12 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Operating efficiency (LOR) | 0,33 |
| Number of luminaires at LS B16A | 61 |
| Number of luminaires at LS C16A | 61 |
| Level of inrush current | 9 A |
| Duration of inrush current | 150 µs |
| Temperature at glass (light emission) | 40 °C |
| Stroboscopic effect (SVM) | 0.05 |
| Lumen | 470 lm |
| Colour temperature | 3000 Kelvin |
| Color | grey |

Light Source

1319290



| | |
|---------------------|----------|
| CRI | 80 |
| LXXBXX data | L80B50 |
| Service life | 50000 h |
| Risk Group | 0 |
| Width | 37.5 cm |
| Height | 25 cm |
| Depth | 8 cm |
| Net weight | 5.3 kg |
| Gross weight | 5.671 kg |