

Luminaire

Code KUSHI 16 MOBILE

Name KUSHI 16 MOBILE

Measurement

Code 0002FT20


Name KUSHI 16 MOBILE

Luminaire Flux	83.00 lm	Luminaire Power	1.30 W	Efficacy	63.85 lm/W	Efficiency	100.00%
Sources Flux	83.00 lm	Maximum value	83.29 cd/klm	Position	C=0.00 G=76.00	CG	Rotosymmetrical
Round Luminaire		Diam.	160 mm	Height	180 mm		
Round Luminous Area		Diam.	160 mm	Height	120 mm		
Horizontal Luminous Area			0.020106 m2	Emitting area on Plane 180°			0.019200 m2
Emitting area on Plane 0°			0.019200 m2	Emitting area on Plane 270°			0.019200 m2
Emitting area on Plane 90°			0.019200 m2	Glare area at 76°			0.023494 m2
Coordinate system		CG		Symmetry Type			Rotosymmetrical
Date		01-05-2020		Maximum Gamma Angle			180
Measurement Distance		0.00		Measurement Flux			83.00 lm

Luminaire Sources

Line		Flux [lm]	Pow. [W]	Q.ty
Board LED SMD - 1,3W - Nominal Lumen 120lm - 2700K - CRI80		83.00	1.30	1
C.I.E.	22 47 74 49 100			
F UTE	0.49 J + 0.51 T			
		D DIN 5040	C12	
		B NBN	BZ 9 / 0.8 / BZ 8 / 1 / BZ 9 / 2.5 / BZ 8	

Diam=160mm



C Halfplanes

180.0 — 0.0

ULOR 50.70 %

DLOR 49.30 %

RN 50.70 %

