

LED cord dimmer T26.07

Item-no.: 2600x0700(i) (transparent) | 2620x0700(i) (black) | 2660x0700(i) (white)



Suitable for dimmable LED lamps, incandescent, HV- and LV-halogen lamps with magnetic transformer

Operates quietly

Opportunity for optimized and flicker-free dimming of LED-lamps in min. area

No stand-by consumption because of real on / off switch

Overload/short-circuit protection

Integrated protective conductor terminal

Applicable as intermediate and end device due to different connection opportunities

EHMANN advantage – 100 % quality check, 5 years warranty, German manufacturer






EHMANN service – Up to date LED recommendation accessible via imprinted QR-code at any time

EHMANN quality – High-grade manufacturing and reliable function



LED cord dimmer T26.07

Technical data

3 – 35 W LED rated power	7 – 110 W/VA Rated power	230 V ~ (+/- 10%) / 50 Hz Rated voltage
Suitable for dimmable LED lamps, incandescent, HV- and LV-halogen lamps with magnetic transformer		
<p>Operating principle: leading edge</p> <p>Function: On /off via separate switch; dimming via slide switch (for hand- and foot use)</p> <p>Temperature protection: thermal fuse</p> <p>Overload/short circuit protection: fuse 5x20mm T1AH/250 V</p> <p>Max. cord diameter: 6,5 mm</p> <p>Cut-off: Complete cut-off</p> <p>Cycle of operation: >50.000</p> <p>Connection: Screw terminal 0,5 - 1,5 mm² (flexible)</p> <p>Mode of operation: S1</p> <p>Protection class: II</p> <p>Safety class: IP20</p> <p>Contamination level: 1</p>	<div data-bbox="1034 741 1369 1014">  </div> <p>Checked by:</p> <div data-bbox="1050 1173 1201 1319">  </div>	
<p>Opportunity for optimized and flicker-free dimming of LED lamps</p> <p>In emergence of flickering-effects during dimming an LED lamp, there is the possibility of adjusting the minimum brightness, in order to optimize the dimming behaviour.</p> <div data-bbox="331 1615 432 1704">  </div>	<p>LED recommendation</p> <p>Shows which LEDs are compatible with this dimmer.</p> <p>Available via QR code or online at www.ehmann-gmbh.de</p> <div data-bbox="715 1585 852 1727">  </div>	<p>Connection diagram as intermediate or end device</p> <div data-bbox="1011 1464 1401 1787">  </div>
<p>Item-no. 2600x0700(i) (transparent) EAN 401209600446 2 PU 10</p> <p>Item-no. 2620x0700(i) (black) EAN 401209600384 7 PU 10</p> <p>Item-no. 2660x0700(i) (white) EAN 401209600385 4 PU 10</p>	<p>130 x 59 x 35 mm Dimensions (L x W x H)</p>	