

Fabbian

DATA SHEET
SCHEMA TECNICA


AKOYA F61D11

CE 220/240V
50/60Hz




IP40

MADE IN
ITALY




Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

AKOYA wall




AKOYA F61D11

CE 220/240V
50/60Hz




IP40

MADE IN
ITALY



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

POTENZA NOMINALE NOMINAL POWER COMSUPTION	7W
POTENZA SORGENTE LUMINOSA SOURCE POWER	6W
ALIMENTAZIONE SUPPLY VOLTAGE	230V 50/60Hz
COLLEGAMENTO CONNECTION	Alla tensione di rete To mains
DIMMERABILITA' DIMMER	1-10V
NR E TIPO LED NR AND TYPE OF LED	1 Power LED Nichia NV4L144AR
DURATA MEDIA LED AVERAGE LED LIFE	50000 ore L90B10 50000 hours L90B10
CCT CCT	3000K
CRI CRI	90+
SELEZIONE BINING	3 MacAdam Step
ANGOLO EMISSIONE OTTICA LIGHT OPTICAL BEAM	Diffusa Diffused
FLUSSO SORGENTE SOURCE FLUX	888lm [3000K, Tj 85°C]
FLUSSO NETTO APPARECCHIO NET FLUX	622lm [3000K, Tj 85°C]
DIMENSIONI DIMENSIONS	Ø300X120mm
PESO NETTO NET WEIGHT	3,38Kg
FISSAGGIO FIXING	A muro con staffa To wall with bracket
MATERIALE CORPO BODY MATERIAL	Lamiera di ferro Steel sheet
MATERIALE SCHERMO SCREEN MATERIAL	Vetro soffiato bianco White blowned glass
FINITURE FINISHING	Verniciato bianco, bronzo, antracite, corten Painted white, bronze, anthracite, corten


AKOYA F61D11

CE 220/240V
50/60Hz




IP40

MADE IN
ITALY



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

TEMPERATURA DI STOCCAGGIO STOCK TEMPERATURE	-20~45°C
TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	-20~45°C
GRADO IP IP GRADE	IP40
GLOW WIRE TEST	960°
TEMPERATURE SCHERMO SCREEN TEMPERATURE	Max 40°C (Ta 25°C)
CLASSE ISOLAMENTO INSULATION CLASS	1
CLASSE EFFICIENZA ENERGETICA ENERGY EFFICIENCY CLASS	Prodotto fornito con sorgente in classe energetica E in accordo with UE 2019/2020 Fixture supplied with light source in energetic class E in accordance with UE 2019/2020
SICUREZZA FOTOBIOLOGICA PHOTOBIOLOGICAL SAFETY	Rischio 1 EN62471:2006 Risk group 1 EN62471:2006

Le informazioni contenute nella presente scheda tecnica possono essere modificate in qualsiasi momento senza preavviso e non comportano l'assunzione, nemmeno implicita, di alcuna obbligazione da parte di Fabbian.
Fabbian Srl reserves the right to change the information contained in this document at any time without prior notice being given.


AKOYA F61D11

CE 220/240V
50/60Hz




IP40

MADE IN
ITALY



Replaceable (LED only) light source by a professional



Replaceable control gear by a professional

Dimensioni - Dimensions:

